
Technical Sheet

RDWF
Dense Drywall Screw

The RDWF screw is recommended for fixing dense plasterboard to timber or light gauge steel from 0.6mm - 1.2mm thick. The reverse thread at the head end of the screw assists with countersinking the head into board. The screw has a reduced bugle head and high-low thread.







Features

Material

Steel - Grey phosphate coating

Benefits

- CE marked to EN14566
- Reduced bugle head
- Sharp point
- High-low thread with reverse thread
- Driver bits included (BIT2PE)

Applications

Support

- For use with drywall or dense drywall board


Common Applications

- Fixing drywall to timber
- Fixing drywall to steel up to 1.2mm thick

Technical Sheet

RDWF
Dense Drywall Screw

Technical Data





Product Dimensions UK

Reference	Fasteners Dimensions							
	Product Dimensions[mm]			QD information			Other	
	Ø Head[mm]	Thread diameter[mm]	l[mm]	Screws qty per strip	Compatible device	Max. rotation speed[tr/min]	Screws qty per box	Weight[kg]
RDWF40BE	6.5	4.2	40	30.0	QDPR051E / QD76KE	2500	2500.0	0.002

RDWF
Dense Drywall Screw

Options





High-Low thread



Tapered tip

Winchester Road Cardinal Point Tamworth Staffordshire
B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®