
Technical Sheet

DWC
Drywall to Timber Screw

The DWC screw is designed for fixing drywall to timber. The screw features a sharp point, coarse thread and bugle head which provides a neat finish in the drywall. The DWC is CE marked to EN14566 and has a grey phosphate coating making it suitable for use indoors.







Features

Material

- Steel - Grey phosphate coating

Benefits

- CE marked to EN14566
- Bugle head
- Sharp point
- Coarse thread
- PH2 driver bits included (BIT2PE)

Applications

Support

- Suitable for fixing to solid wood, composite wood, glued laminate and OSB

Common Applications


- Plasterboard to timber

Technical Sheet

DWC
Drywall to Timber Screw

SIMPSON Strong-Tie

Technical Data





Product Dimensions UK

Reference	Fasteners Dimensions							
	Other		Product Dimensions[mm]			QD information		
	Screws qty per box	Weight[kg]	Ø Head[mm]	Thread diameter[mm]	l[mm]	Screws qty per strip	Max. rotation speed[tr/min]	Compatible device
DWC3525PE	2500.0	0.002	8.1	3.8	25	30.0	2500 - 6000	QDPR051E / QD76KE
DWC3535PE	2500.0	0.002	8.1	3.8	35	30.0	2500 - 6000	QDPR051E / QD76KE
DWC3540PE	2500.0	0.002	8.1	3.8	40	30.0	2500 - 6000	QDPR051E / QD76KE
DWC3545PE	2000.0	0.003	8.1	3.8	45	30.0	2500 - 6000	QDPR051E / QD76KE
DWC3550PE	2000.0	0.003	8.1	3.8	50	30.0	2500 - 6000	QDPR051E / QD76KE
DWC3930PE	2500.0	0.002	8.1	4	30	30.0	2500 - 6000	QDPR051E / QD76KE
DWC3945PE	2000.0	0.003	8.1	4	45	30.0	2500 - 6000	QDPR051E / QD76KE
DWC3965PE	1500.0	0.005	8.1	4	65	30.0	2500 - 6000	QD76KE

DWC
Drywall to Timber Screw

Options





Single Thread



Tapered tip

Winchester Road Cardinal Point Tamworth Staffordshire
B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®