Technical Sheet

RSND34G

Framing Nail 34° Paper tape - Clipped Head, Ring shank - HDG

The framing nail is used for wood to wood constructions. The clipped head and the tight collation means that more nails can be loaded in the tools and the ring shank increases the withdrawal capacity.







Features

Advantages

- Clipped head (D-head)
- High withdrawal capacity
- Hot dip galvanised
- Annular ring thread
- Paper tape 34°

Applications

Support

- Framing wood to wood

RSND34G

Framing Nail 34° Paper tape - Clipped Head, Ring shank - HDG

Technical Data

Product dimensions

Reference	Fasteners Dimensions									
	Item Code	Other			Product Dimensions[mm]					
		Tun / DB nr.	NOB nr.	Weight[kg]	d[mm]	l[mm]	dh[mm]	A_h[mm]	ht[mm]	tfix[mm]
RSND34G2.8X65	75762	2056109	55837755	0.004	2.8	65	5	19.6	1.1	48.2
RSND34G2.8X75	75763	2056110	55837766	0.004	2.8	75	5	19.6	1.1	58.2

Product characteristic properties

Reference	Nail characteristic parameters			
	Characteristic parameters			
	Characteristic Yield Moment My,k[Nm]	Characteristic Withdrawal Parameter fax,k,90°[N/mm²]	Characteristic Head Pull-Through Parameter fhead,k[N/mm²]	Characteristic tensile capacity - $f_{tens,k}$[kN]
RSND34G2.8X65	3.2	9.3	22.9	3.1
RSND34G2.8X75	3.2	9.3	22.9	3.1

Winchester Road Cardinal Point
Tamworth Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®