Technical Sheet

BRDC

Grooved Countersunk Nail - Lacquered

Nail with a countersunk head and grooved shank. Use indoors for fastening painted woodwork to timber or mouldings and other types of fine joinery.





Features

Features

- Countersunk head.
- Grooved thread.
- Carbon steel - lacqured.

Applications

Suitable For

- Wood to wood.

Technical Sheet

BRDC
Grooved Countersunk Nail - Lacquered

Technical Data



Dimensions and drill holes

Reference	Fasteners Dimensions							
	Item Code	Other				Product Dimensions[mm]		
		Tun / DB nr.	NOB nr.	Qty per blister	Weight[kg]	d[mm]	l[mm]	dh[mm]
BRDC1.7X35	74203	1950531	53291904	-	0.001	1.7	35	2.7
BRDC1.7X40	74204	1950532	53291912	-	0.001	1.7	40	2.7
BRDC2.0X50	74205	1950533	53291923	-	0.001	2	50	3.2

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®