Technical Sheet

CBR
Masonry Reinforcement Mesh

Provide added strength and stability.


- *Galvanised or stainless steel finish.*
- *Assists resistance to tensile stresses where settlement occurs. Easily incorporated into mortar course, coiled for ease of handing.*

Installation:

- *All metal components used in any particular application must be of the same material type.*
- *Gloves should be worn to protect hands from sharp metal edges.*
- *Position the mesh within the masonry bed joints, providing a minimum of 25mm cover to external faces.*
- *Overlap by a minimum of 75mm if joining two lengths together. The mesh can be laid every third brickwork course for most reinforcement.*







Features

Installation

- All metal components used in any particular application must be of the same material type.
- Gloves should be worn to protect hands from sharp metal edges.
- Position the mesh within the masonry bed joints, providing a minimum of 25 mm cover to external faces.
- Overlap by a minimum of 75 mm if joining two lengths together. The mesh can be laid every third brickwork course for most reinforcement.

Technical Sheet


CBR
Masonry Reinforcement Mesh

Technical Data

Product Dimensions

Reference	Connector Dimensions		
	Other		Dimensions
	Material	Weight[kg]	
CBR2063	Galvanised	0.75	63mm x 20m
CBR2063S	Stainless Steel	1.1	63mm x 20m
CBR20112	Galvanised	1.4	112mm x 20m
CBR20112S	Stainless Steel	1.4	112mm x 20m
CBR20175	Galvanised	3	175mm x 20m
CBR20175S	Stainless Steel	3	175mm x 20m
CBR20228	Galvanised	2.8	228mm x 20m
CBR20228S	Stainless Steel	5.7	228mm x 20m
CBR20305	Galvanised	3.8	305mm x 20m

Installation



Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®