Technical Sheet

MKSA4

Ring Shank Brick/Wood to Wood Nail

This ring shank nail in stainless steel can withstand rain and aggressive environments. Used where high withdrawal strength is required. A common use is in the construction of jetties, thanks to the nail's corrosion resistance. When laying a brick facade the joins are anchored to an existing cross-wall up to 6 m.






Technical Sheet

MKSA4
Ring Shank Brick/Wood to Wood Nail

Technical Data

Product Dimensions



Reference	Fasteners Dimensions										
	Item Code	Other			Product Dimensions[mm]						
		NOB nr.	Tun / DB nr.	Weight[kg]	d[mm]	l[mm]	dh[mm]	A_h[mm]	ht[mm]	lg[mm]	lp[mm]
MKSA44.0X100	74229	53292892	1950558	0.011	4	100	8.5	56.7	2	50	5

Product characteristic properties

Reference	Nail characteristic parameters			
	Characteristic parameters			
	Characteristic Yield Moment My,k[Nm]	Characteristic Withdrawal Parameter fax,k,90°[N/mm²]	Characteristic Head Pull-Through Parameter fhead,k[N/mm²]	Characteristic tensile capacity - $f_{tens,k}$[kN]
MKSA44.0X100	7825	6.2	-	8.3
Refer to relevant ITTR or ETA for more details				

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®