Technical Sheet

FLB
Washbasin and bidet wall fixing

Applications

Applications

- Washbasins
- Sanitary items

Suitable for:

- Non-cracked concrete
- Honeycomb brick
- Aerated concrete
- Solid stone
- Solid brick (partially suitable)
- Lightweight honeycomb brick (partially suitable)
- Hollow dense aggregate block (partially suitable)
- Hollow light aggregate block (partially suitable)






Technical Sheet

FLB
Washbasin and bidet wall fixing

Technical Data






Product Dimension


Reference	Fixing installation dimensions												
	Product reference	Type [d_mxLv]	Fixture thickness [t_{fix}]	Hole diameter [d_o]	Minimum hole depth [h_1]	Nominal embedment depth [h_{nom}]	Minimum support thickness [h_{min}]	Screw diameter [d]	Bush diameter [d_P]	Wrench	Qty per box	Qty per outer box	Weight[kg]
61407B081100C	FLB	M8x110	30	10	70	60	100	8	11,5	13	2.0	25.0	0.052
61407B101000C	FLB	M10x100	20	12	70	60	100	10	13,6	17	2.0	25.0	0.073
61407B101200C	FLB	M10x120	40	12	70	60	100	10	13,6	17	2.0	25.0	0.083
61407B101400C	FLB	M10x140*	40	14	90	80	120	10	13,6	17	2.0	25.0	0.098


* *Plug 14x80 plug with greater nylon thickness.*


FLB
Washbasin and bidet wall fixing


Installation











Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®