Technical Sheet

CLSZN
Wood Facade Screw - Impreg®+

The CLSZN is a double threaded screw suitable for use with timber cladding. The screw consists of type 17 point to prevent timber splitting on insertion and flat head with fiber lock technology which prevents moisture getting into the timber. The double thread ensures sufficient insertion, even in high density wood without the risk of spin-off. It also helps pull the cladding tight to the frame. The CLSZN screw has Impreg®+ coating and as therefore suitable for use in outdoor environments.







Features

Material

Steel - Impreg®+ coating

Features

- 6 lobe drive
- Flat head with fiber lock technology
- Double threaded
- Extreme ductility
- Type 17 point

Applications


Common Applications

- Cladding to timber
- Timber facades to timber

Technical Sheet

CLSZN
Wood Facade Screw - Impreg®+

Technical Data



Products dimensions

Reference	Fasteners Dimensions						
	Other	Product Dimensions[mm]					
	Box Quantity	d[mm]	l[mm]	dh[mm]	lg1[mm]	lg2[mm]	bit[mm]
CLSZN4.8X48	250.0	4.8	48	8	26	18	T-20
CLSZN4.8X65	250.0	4.8	65	8	26	22	T-20

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616
Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®