Technical Sheet

WSHL
WSHL45E UNDERLAYMENT to Wood Screw

WSHL45E has a sharp point with a hi-lo thread design. Suitable for fast and secure fixing of fiberboard, Fermacell, plywood and OSB to timber or light gauge steel frames. Maximum steel frame thickness of 0.9mm. Also suitable for fixing timber to timber such as flooring applications.







Features

Material

- Steel - phosphate coating

Features

- Rimmed flat head with nibs for easy countersinking
- High-low thread
- Sharp point
- Bit (BIT2SE) included

Applications

Support


- Underlayment

Applications

- Fermacell board to timber
- Fermacell board to light gauge steel
- Subfloor to timber
- plywood/OSB to timber/light gauge steel

WSHL
WSHL45E UNDERLAYMENT to Wood Screw

Technical Data



Product Dimensions

Reference	Fasteners Dimensions					
	Other	Product Dimensions[mm]				QD information
	Weight[kg]	Thread Diameter[mm]	Total Length[mm]	Head diameter[mm]	lg[mm]	Qty per Strip
WSHL45E	5.5	3.8	45	7.5	31	30.0

Winchester Road Cardinal Point Tamworth
Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®